E06-B206E

Laser Projector Light Output	5,000 lm
Projector Color Gamut Standard	DCI
Laser Projector Contrast	2000:1
Light Source Service Life	30,000 hours
Light Source Operating Voltage	200~240V
Light Source Power Consumption	550W
Operating Environment Temperature	10-35°C
Cooling Technology	Air Cooling
Light source kit package	745×480×400mm / 20kg
Applicable Projector(s)	DP2K-6E

E10-B210S

Laser Projector Light Output	10,000 lm
Projector Color Gamut Standard	DCI
Laser Projector Contrast	2000:1
Light Source Service Life	30,000 hours
Light Source Operating Voltage	200~240V
Light Source Power Consumption	1KW
Operating Environment Temperature	10-35°C
Cooling Technology	Air Cooling
Light source kit package	745×545×380mm / 26kg
Applicable Projector(s)	DP2K-8S/10S

E12-B212C

Laser Projector Light Output	12,000 lm
Projector Color Gamut Standard	DCI
Laser Projector Contrast	2400:1
Light Source Service Life	30,000 hours
Light Source Operating Voltage	200~240V
Light Source Power Consumption	1.2KW
Operating Environment Temperature	10-35°C
Cooling Technology	Air Cooling
Light source kit package	775×502×425mm / 30kg
Applicable Projector(s)	DP2K-12C

E15-B215C

Laser Projector Light Output	15,000 lm
Projector Color Gamut Standard	DCI
Laser Projector Contrast	2400:1
Light Source Service Life	30,000 hours
Light Source Operating Voltage	200~240V
Light Source Power Consumption	1.35KW
Operating Environment Temperature	10-35°C
Cooling Technology	Air Cooling
Light source kit package	775×502×425mm / 30kg
Applicable Projector(s)	DP2K-15C

E19-B2XXB

Laser Projector Light Output	18,000 lm
Projector Color Gamut Standard	DCI
Laser Projector Contrast	2400:1
Light Source Service Life	30,000 hours
Light Source Operating Voltage	200~240V
Light Source Power Consumption	1.5KW
Operating Environment Temperature	10-35°C
Cooling Technology	Air Cooling
Light source kit package	760×610×448mm / 35kg
Applicable Projector(s)	DP2K/4K-19B/23B/32B

E20-B220C

Laser Projector Light Output	20,000 lm
Projector Color Gamut Standard	DCI
Laser Projector Contrast	2400:1
Light Source Service Life	30,000 hours
Light Source Operating Voltage	200~240V
Light Source Power Consumption	1.86KW
Operating Environment Temperature	10-35°C
Cooling Technology	Air Cooling
Light source kit package	775×502×425mm / 30kg
Applicable Projector(s)	DP2K-18Cx/20C

E25-B2XXB

Laser Projector Light Output	25,000 lm
Projector Color Gamut Standard	DCI
Laser Projector Contrast	2400:1
Light Source Service Life	30,000 hours
Light Source Operating Voltage	200~240V
Light Source Power Consumption	1.86KW
Operating Environment Temperature	10-35°C
Cooling Technology	Air Cooling
Light source kit package	760×610×448mm / 35kg
Applicable Projector(s)	DP2K/4K-23B/32B

E30-B2XXB

Laser Projector Light Output	30,000 lm
Projector Color Gamut Standard	DCI
Laser Projector Contrast	2400:1
Light Source Service Life	30,000 hours
Light Source Operating Voltage	200~240V
Light Source Power Consumption	2.5KW
Operating Environment Temperature	10-35°C
Cooling Technology	Air Cooling
Light source kit package	950×455×475mm / 43.8kg
Applicable Projector(s)	DP2K/4K-32B

E40-B2XXB

Laser Projector Light Output	38,000 lm
Projector Color Gamut Standard	DCI
Laser Projector Contrast	2400:1
Light Source Service Life	30,000 hours
Light Source Operating Voltage	200~240V
Light Source Power Consumption	3.4KW
Operating Environment Temperature	10-35°C
Cooling Technology	Air Cooling
Light source kit package	950×455×475mm / 43.8kg
Applicable Projector(s)	DP2K/4K-32B